

ATLAS 10 AIRLESS SPRAYER

Tough Sprayers For The Toughest Jobs

Painttechnik ATLAS 10 inch series airless sprayer with a new outlook and more powerful pump. Our new technology and high quality pump gives you great performance and additional power. The ATLAS 10 pump is easy to disassemble which aids greatly for maintenance and troubleshooting.

ATLAS 10 is highly reliable and suited to the harshest environments. It can handle extremely viscous fluids which require extreme pressure ratios and high flow rates.

The Painttechnik ATLAS 10 airless sprayer with high quality motor and pump is the answer for your heavy duty spray applications.

Advantages of the ATLAS 10

- The latest technology air motor
- Higher pressure ratio for higher flow rates, longer lines and better atomization
- Wide spraying and coating covered area
- Simple maintenance and fluid section

Typical Applications

- Marine and shipyard - Off-shore - Railcars and other transport vehicles - Chemical and petrochemical plants - Public work facilities - Pulp and paper mills - Nuclear and conventional power facilities - Pipeline - Metals and mining



Category	Model			
	PT0110	PT0115	PT0116	PT0118
Pressure Ratio	45:1	65:1	70:1	80:1
Max. Fluid Working Pressure	5220psi (360BAR)	6500psi (455BAR)	7000psi (490BAR)	7400psi (510BAR)
Max. Air Input Pressure	116psi (8.0BAR)	100psi (7.0BAR)	100psi (7.0BAR)	92.5psi (6.4BAR)
Max. Volume Flow Rate	15lpm (4.09gpm)	11.7lpm (3.1gpm)	10.8lpm (2.85gpm)	8.7lpm (2.3gpm)
Volume Per Cycle	250cc	195cc	180cc	145cc
Max. Rec. Pump Speed	60 CPM			
Air Inlet Size	3/4" PT			
Fluid Inlet Size	1" PT			
Fluid Outlet Size	1/4" PT or 3/8" PT			